




COMMITTED TO XCELLENCE™

FD7931/41T 17" Open Frame Display



Classic for today's retail, POS, Kiosk and Industry applications, the FD7931/41T model supports touch screen, as like 5-Wire Resistive, by USB interface for use in retail trade environments which requires a rugged touch function. It also offers many upgraded features such as wide-view angle, high contrast ratio and faster response time. In a brief and technological term, FD7931/41T model is designed to work with most systems, such as x86 and RISC based ones by its powerful Scaler IC and excellent structure. Thus, Analog signals, VGA/DVI/SV/AV interfaces could be processed precisely by its specific design. The Result is an exceptional durable touch monitor and an excellent value.

Features



Specification Overview:

Viewable Size:	17" LCD Diagonal
Resolution:	1280 X 1024 (SXGA)
Controller Interface:	USB
Contrast Ratio:	500:1ms (Typical)
Brightness:	300 nit (cd/m ²)
Viewing Angle (H/V):	150° / 130°
Response Time:	8ms
Colour:	16.2 Million
OSD Control:	Keys: Auto Tune, Menu, Decrease, Increase, Functions: Brightness, Contrast, Clock, Phase Horizontal/ Vertical Position,
I/O Interface:	VGA / DVI / USB For FD7931T VGA / DVI / SV / AV/ USB For FD7941T
Scanning Freq.:	24~80Khz/ 56~75Hz
Plug & Play	VESA DDC 2B Compatible
Power Input:	12 VDC(AC 90 ~ 240V (50/60Hz))
Power Consumption:	48W Max., (2W Max. Off Mode)
Dimension (W x H x D):	439 x 345 x 58.8 mm
Net Weight/ Gross Weight:	6.1Kg