



1/3" IR Color CCD Camera

CM-D3300

Feature

- Plastic housing / Indoor
- DC 12V / IR Distance : 4M
- 420 TVLines / Board lens : 3.6mm / 4.3mm



Specification

	CM-D3300
Video System	NTSC / PAL
Pick up device	1/3" image sensor interline transfer CCD
Total Pixels	NTSC : 537(H) x 505(V) / PAL : 537(H) x 597(V)
Effective Pixels	NTSC : 510(H) x 492(V) / PAL : 500(H) x 582(V)
Resolution	420 TV lines
Sync. System	Internal Sync.
Scanning System	NTSC: 525Lines / 60Fields ; PAL : 625Lines / 50Fields
S/N Ratio	More than 48 dB(AGC OFF)
Electronic Shutter	1/60-1/100,000 sec. ; 1/50-1/100,000 sec.
Min. Illumination	0.5 lux color / F1.2
Video Output	1.0 Vp-p / 75 ohm composite
Scanning System	NTSC:15.734 Khz ; PAL:15.625 Khz
Gamma Correct	0.45
White Balance Control	Auto
Lens Mount Type	Board Lens 3.6mm / 4.3mm
DC power Source	DC12V
Dimension	92mm (Diameter) x 73(H)mm
Operation Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)

Dimension

